Product datasheet

Specifications



APC NetShelter Basic Rack PDU, Zero U, 11 kW, 230V, 36 C13 and 6 C19 outlet, IEC309 inlet

AP7557

Main

Product or component type	PDU
Main Input Voltage	400 V 3 phases
Input current limits	16 A
Network frequency	50/60 Hz
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 3P + N + PE
Number of power socket outlets	36 IEC 60320 C13 6 IEC 60320 C19
Load capacity	11000 VA
Max current draw	16 A
PDU type	Basic
Protection type	Without circuit breaker
Number of rack unit	0U
Number of cables	1
Cable length	0.9 m
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit User manual

Complementary

Mounting location	Side
Mounting mode	Rack-mounted
Mounting position	Vertical
Height	1778 mm
Width	56 mm
Depth	44 mm
Net weight	5.45 kg

Environmental

Product certifications	C-Tick CE GOST MIC Queensland Australia VDE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	8.841 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**3 371 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.6 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.6 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**3 339 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.6 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**45**
End of life manual availability	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative





